

Quality-Assurance Data for Routine Water Analyses by the U.S. Geological Survey Laboratory in Troy, New York— July 1999 through June 2001



Open-File Report 2006-1246

U.S. Department of the Interior U.S. Geological Survey

Cover. Purple aster with fly, Warwick, New York ©2006 M. Peter deVries

Quality-Assurance Data for Routine Water Analyses by the U.S. Geological Survey Laboratory in Troy, New York— July 1999 through June 2001

By Tricia A. Lincoln, Debra A. Horan-Ross, Michael R. McHale, and Gregory B. Lawrence

Open-File Report 2006–1246

U.S. Department of the Interior U.S. Geological Survey

U.S. Department of the Interior

DIRK KEMPTHORNE, Secretary

U.S. Geological Survey

Mark D. Myers, Director

U.S. Geological Survey, Reston, Virginia: 2006

For more information on the USGS--the Federal source for science about the Earth, its natural and living resources, natural hazards, and the environment: World Wide Web: http://www.usgs.gov Telephone: 1-888-ASK-USGS

Any use of trade, product, or firm names is for descriptive purposes only and does not imply endorsement by the U.S. Government.

Although this report is in the public domain, permission must be secured from the individual copyright owners to reproduce any copyrighted materials contained within this report.

Suggested citation:

Lincoln, T.A., Horan-Ross, D.A., McHale, M.R., and Lawrence, G.B., 2006, Quality-Assurance Data for Routine Water Analyses by the U.S. Geological Survey Laboratory in Troy, New York—July 1999 through June 2001: U.S. Geological Survey Open-File Report 2006-1246, 27 p., online only.

Contents

| Abstract1 |
|--|
| Introduction1 |
| Purpose and Scope2 |
| Participating Projects2 |
| Quality-Assurance/Quality-Control (QA/QC) Program2 |
| Quality-Control Samples |
| Filter Blanks and Analytical Blanks3 |
| Triplicate Environmental Samples3 |
| U.S. Geological Survey's Standard Reference Sample Project |
| NWRI Ecosystem Interlaboratory QA Program4 |
| Blind Reference Samples4 |
| Control-Chart Evaluation |
| Quality-Control Samples5 |
| Filter Blanks and Analytical Blanks5 |
| Triplicate Environmental Samples5 |
| NWRI Ecosystem Interlaboratory QA Program5 |
| Blind Reference Samples5 |
| Summary of Results |
| A. Quality-Control Samples6 |
| B. Filter Blanks and Analytical Blanks7 |
| C. Triplicate Environmental Samples8 |
| D. U.S. Geological Survey's Standard Reference Sample (SRS) Project8 |
| E. NWRI Ecosystem Interlaboratory QA Program10 |
| F. Blind Reference Samples10 |
| Selected References |

Figures

| 1–5 | Graphs showing— | |
|-----|--|-----|
| | 1. High- and low-concentration quality-control sample results: | |
| | A. Acid-neutralizing capacity | .14 |
| | B. Aluminum, total monomeric | .14 |
| | <i>C</i> . Aluminum, total | .14 |
| | D. Ammonium | .14 |
| | <i>E</i> . Calcium | .15 |
| | F. Carbon, dissolved organic | |
| | G. Chloride | .15 |
| | H. Fluoride | |
| | I. Magnesium | |
| | J. Nitrate (ion chromatography) | .16 |
| | K. Nitrate (colorimetric method) | .16 |
| | <i>L</i> . pH | .16 |
| | м. Potassium | .17 |
| | N. Silicon | |

| | <i>O</i> . Sodium | 17 |
|----|--|----|
| | P. Specific conductance | 17 |
| | Q. Sulfate | |
| 2 | Filter-blank and analytical-blank sample results: | |
| ۷. | A. Aluminum, total monomeric | 10 |
| | | |
| | B. Aluminum, organic monomeric | |
| | C. Aluminum, total | |
| | D. Ammonium | |
| | E. Calcium | |
| | F. Carbon, dissolved organic | |
| | G. Chloride | |
| | H. Fluoride | 19 |
| | I. Magnesium | 20 |
| | J. Nitrate (ion chromatography) | 20 |
| | K. Potassium | |
| | L. Silicon | |
| | <i>M</i> . Sodium | |
| | N. Specific conductance | |
| | <i>O</i> . Sulfate | |
| ~ | | 20 |
| 3. | Triplicate environmental sample results: | |
| | A1. Acid-neutralizing capacity (for triplicate means not in $\pm 20 \ \mu eq/L$ range) | |
| | A2. Acid-neutralizing capacity (for triplicate means in $\pm 20 \ \mu eq/L$ range) | |
| | B. Aluminum, total monomeric | |
| | C. Aluminum, organic monomeric | 21 |
| | D. Aluminum, total | 21 |
| | E. Ammonium | 21 |
| | <i>F</i> . Calcium | 21 |
| | G. Carbon, dissolved organic | 21 |
| | H. Chloride | |
| | <i>I</i> . Fluoride | |
| | J. Magnesium | |
| | K. Nitrate (ion chromatography) | |
| | <i>L</i> . pH | |
| | <i>M</i> . Potassium | |
| | N. Silicon | |
| | | |
| | 0. Sodium | |
| | P. Specific conductance | |
| | <i>Q.</i> Sulfate | 23 |
| 4. | NWRI Ecosystem Interlaboratory QA Program results: | |
| | A1. Acid-neutralizing capacity (for samples not in the range of \pm 20 μ eq/L) | 24 |
| | A2. Acid-neutralizing capacity (for samples in the range of \pm 20 μ eq/L) | 24 |
| | B. Aluminum, total | 24 |
| | C. Ammonium | 24 |
| | D. Calcium | 24 |
| | E. Carbon, dissolved organic | |
| | <i>F</i> . Chloride | |
| | G. Magnesium | |
| | H. Nitrate (ion chromatography) | |
| | | |
| | / pH | |
| | J. Potassium | |
| | K. Silicon | |
| | <i>L</i> . Sodium | 25 |

| | M. Specific conductance | 25 |
|----|---------------------------------|----|
| | N. Sulfate | |
| 5. | Blind reference sample results: | |
| | A. Calcium | 26 |
| | B. Chloride | |
| | C. fluoride | 26 |
| | D. Magnesium | 26 |
| | Е. рН | 26 |
| | F. Potassium | 26 |
| | G. Sodium | 26 |
| | H. Specific conductance | 26 |
| | I. Sulfate | |
| | | |

Tables

| 1. | Number of environmental and quality-control (QC) samples analyzed by the Troy Laboratory, and summary of quality-control data for each constituent, July 1999 through June 2001 | 4 |
|----|--|---|
| 2. | Reporting limits and data-quality objectives for accuracy, precision, and blanks for solution analyses performed by the U.S. Geological Survey Laboratory in Troy, N.Y., July 1999 through June 2001 | 6 |
| 3. | Results obtained by the Troy Laboratory for the U.S. Geological Survey Standard Reference Sample (SRS) Project, Octobber 1999 through October 2000 | 9 |

ABBREVIATED UNITS OF MEASUREMENT

- mg/L milligrams per liter
- μeq/L microequivalents per liter
- µmol/L micromoles per liter
- μS/cm microsiemens per centimeter
- μg/L micrograms per liter

Other Abbreviations

| ANC | Acid-neutralizing capacity |
|---------|---|
| AV | Analyzed value |
| CV | Coefficient of variation |
| D | Percent difference |
| DI | Deionized water |
| DOC | Dissolved organic carbon |
| DQO | Data-quality objective |
| MCV | Mean concentration value |
| MPV | Most probable value |
| NWRI | National Water Research Institute |
| QA | Quality assurance |
| OC | Quality control |
| QC-high | High-concentration quality-control sample |
| QC-low | Low-concentration quality-control sample |
| SRS | Standard Reference Sample |
| TV | Troy Laboratory value |
| USGS | U.S. Geological Survey |

Quality-Assurance Data for Routine Water Analyses by the U.S. Geological Survey Laboratory in Troy, New York— July 1999 through June 2001

By Tricia A. Lincoln, Debra A. Horan-Ross, Michael R. McHale, and Gregory B. Lawrence

Abstract

The laboratory for analysis of low-ionic-strength water at the U.S. Geological Survey (USGS) Water Science Center in Troy, N.Y., analyzes samples collected by USGS projects throughout the Northeast. The laboratory's quality-assurance program is based on internal and interlaboratory qualityassurance samples and quality-control procedures that were developed to ensure proper sample collection, processing, and analysis. The quality-assurance and quality-control data were stored in the laboratory's LabMaster data-management system, which provides efficient review, compilation, and plotting of data. This report presents and discusses results of qualityassurance and quality-control samples analyzed from July 1999 through June 2001.

Results for the quality-control samples for 18 analytical procedures were evaluated for bias and precision. Control charts indicate that data for eight of the analytical procedures were occasionally biased for either high-concentration or low-concentration samples but were within control limits; these procedures were: acid-neutralizing capacity, total monomeric aluminum, total aluminum, calcium, chloride and nitrate (ion chromatography and colormetric method) and sulfate. The total aluminum and dissolved organic carbon procedures were biased throughout the analysis period for the high-concentration sample, but were within control limits. The calcium and specific conductance procedures were biased throughout the analysis period for the low-concentration sample, but were within control limits. The magnesium procedure was biased for the high-concentration and low concentration samples, but was within control limits.

Results from the filter-blank and analytical-blank analyses indicate that the procedures for 14 of 15 analytes were within control limits, although the concentrations for blanks were occasionally outside the control limits. The dataquality objective was not met for dissolved organic carbon.

Sampling and analysis precision are evaluated herein in terms of the coefficient of variation obtained for triplicate samples in the procedures for 17 of the 18 analytes. At least 90 percent of the samples met data-quality objectives for all analytes except ammonium (81 percent of samples met objectives), chloride (75 percent of samples met objectives), and sodium (86 percent of samples met objectives).

Results of the USGS interlaboratory Standard Reference Sample (SRS) Project indicated good data quality over the time period, with most ratings for each sample in the good to excellent range. The P-sample (low-ionic-strength constituents) analysis had one satisfactory rating for the specific conductance procedure in one study. The T-sample (trace constituents) analysis had one satisfactory rating for the aluminum procedure in one study and one unsatisfactory rating for the sodium procedure in another. The remainder of the samples had good or excellent ratings for each study.

Results of Environment Canada's National Water Research Institute (NWRI) program indicated that at least 89 percent of the samples met data-quality objectives for 10 of the 14 analytes; the exceptions were ammonium, total aluminum, dissolved organic carbon, and sodium. Results indicate a positive bias for the ammonium procedure in all studies. Data-quality objectives were not met in 50 percent of samples analyzed for total aluminum, 38 percent of samples analyzed for dissolved organic carbon, and 27 percent of samples analyzed for sodium.

Results from blind reference-sample analyses indicated that data-quality objectives were met by at least 91 percent of the samples analyzed for calcium, chloride, fluoride, magnesium, pH, potassium, and sulfate. Dataquality objectives were met by 75 percent of the samples analyzed for sodium and 58 percent of the samples analyzed for specific conductance.

Introduction

The U.S. Geological Survey (USGS) maintains a laboratory at its Water Science Center in Troy, N.Y., to analyze low-ionic-strength water for USGS watershedresearch projects that require major-ion analyses of precipitation, soil-water, shallow ground-water, and

2 Quality-Assurance Data for Routine Water Analyses by the USGS Laboratory in Troy, New York, July 1999 through June 2001

stream-water samples. The methods used in this laboratory are described in detail in Lawrence and others (1995). The entire historical database was moved from the laboratory's SAS data-management system to a LabMaster laboratory information management system in January 2000. Qualityassurance and quality-control data were then collected, stored, and reviewed through the laboratory's LabMaster information management system for the remainder of this report period (July 1999-June 2001).

The 18 analytes represented by this study were: acid-neutralizing capacity (ANC), total monomeric aluminum, organic monomeric aluminum, total aluminum, ammonium, calcium, dissolved organic carbon (DOC), chloride, fluoride, magnesium, nitrate (ion chromatograph and colorimetric method), pH, potassium, silicon, sodium, specific conductance, and sulfate.

Purpose and Scope

This report documents the quality-assurance practices and quality-control data of this laboratory and is intended for use by cooperating agencies. It (1) describes qualitycontrol and quality-assurance procedures of the laboratory; (2) presents graphs showing the results from analyses of quality-control samples, filter blanks and analytical blanks, triplicate environmental samples, interlaboratory quality-assurance samples, and blind reference samples; and (3) describes analytical biases and outliers and the corrective actions taken.

Participating Projects

The numbers and types of samples analyzed by the laboratory during the 2-year period are summarized below, by the project for which they are associated.

Project: Neversink Watershed StudyCooperator: New York City Department ofEnvironmental ProtectionAnalyses: 176 samples (stream water, shallow ground water, and snow).

Project: Biogeochemical Processes that Control Nitrogen Cycling and Associated Hydrogen and Aluminum Leaching in an Undeveloped Headwater Basin **Cooperator:** New York City Department of Environmental Protection

Analyses: 2,354 samples (stream water, shallow ground water, soil-water solution, soil-water by expulsion method, and snow).

Project: Long-Term Monitoring of Five Streams in the Catskill MountainsCooperator: U.S. Environmental Protection AgencyAnalyses: 610 stream-water samples.

Project: The Effects of the Clean Air Act on Water Quality of Medium-Scale Rivers in the Northeastern United States **Cooperator:** U.S. Geological Survey, Office of Water Quality **Analysis:** 667 stream-water samples.

Project: Adirondack Effects Assessment Program **Cooperator:** Rensselaer Polytechnic Institute **Analyses:** 442 stream-water samples.

Project: Upper and Lower Node Water-Quality Operation and Maintenance in the Catskill Mountains, New YorkCooperator: New York City Department ofEnvironmental ProtectionAnalyses: 735 stream-water samples.

Project: Hydrologic Geomorphology, Water Quality, and Biology of the Neversink River **Cooperator:** Town of Thompson, New York **Analysis:** 162 stream-water samples.

Project: Collaborative Environmental Monitoring and Research Initiative|
Cooperator: U.S. Geological Survey, Office of Water Quality and U.S. Forest Service
Analyses: 32 stream-water samples.

Additional information on projects of the New York Water Science Center is given at http://ny.water.usgs.gov.

Quality-Assurance/Quality-Control (QA/QC) Program

The quality of the data produced at this laboratory is maintained by adherence to the standard operating procedures described in Lawrence and others (1995) and by participation in externally administered quality-assurance (QA) programs. Results of QA data are evaluated by the laboratory supervisor and primary analysts, and appropriate corrective action is taken when needed. The data-quality objectives (DQOs) are based on (1) the precision and accuracy levels generally required by projects that use the Troy Laboratory, and (2) the analytical limits of the methods used.

Quality-Control Samples

Quality-control (QC) samples are used to measure the accuracy of an instrument's calibration and to detect variations in instrument response within an analytical run. Source material for all QC samples either is obtained from a manufacturer other than the producer of the source material used to make calibration standards, or is obtained from a lot other than the source material used to make calibration standards.

The concentrations of QC samples are chosen to bracket the expected range of the environmental sample concentrations. A high-concentration QC sample and a low-concentration QC sample (referred to herein as QC-high and QC-low) are prepared for most analyses; exceptions are organic monomeric aluminum, for which column efficiency is used to determine the acceptability of the data, and fluoride, for which only one mid-level QC sample is prepared because the concentrations encountered by the laboratory are within a narrow range.

QC-high and QC-low samples are analyzed within a run for most constituents; exceptions are ANC, pH, and specific conductance. Either the QC-high sample or QC-low sample is analyzed within an ANC, pH, and specific conductance run, depending upon the expected concentration range of the environmental samples.

Quality-control samples are analyzed immediately after instrument calibration, after every 10 analyses of environmental samples, and at the end of each run. QC samples that do not meet DQOs for accuracy are rerun, and if the value is acceptable, the run is continued. If the rerun QC sample value is unacceptable, the environmentalsample data preceding it are considered to be out-ofcontrol, the data are rejected, and the instrument is recalibrated. Only accepted QC-sample and environmentalsample data are entered into the database. An exception to this practice occurs when the volume of an environmental sample is insufficient for a rerun; in this case, the environmental sample and QC data are entered into the database and flagged, and the project chief then decides whether to use or exclude these data from their reports. The analytical results of QC samples in this report indicate (1) the frequency of out-of-control data that are not rerun, and (2) biases and trends of control data. The numbers of samples analyzed and a summary of the quality-assurance data are given in table 1.

Filter Blanks and Analytical Blanks

A filter blank and an analytical blank are included in each group of 50 environmental samples.

Filter blanks are aliquots of deionized (DI) water that are processed and analyzed in the same manner as environmental samples. Filter blanks are analyzed only for constituents that

require filtration. Filter-blank analysis indicates whether contamination has occurred during any step in sample handling, including bottle-washing procedures, filtration, sample preservation, or laboratory analysis.

Analytical blanks are aliquots of DI water that are processed and analyzed as environmental samples, except that the filtration step is omitted. Contamination found in analytical blanks may be attributed to any step in sample handling, but not to filtration.

Triplicate Environmental Samples

One set of triplicate environmental samples is included in each group of 50 samples. An environmental triplicate set consists of three consecutive samples collected at one field site. The purpose of environmental triplicate samples is to determine long-term analytical precision. Precision can be affected by bottle washing, sample-collection or sampleprocessing procedures, and analysis. Environmental samples are selected for triplicate analysis on a random basis to ensure a wide range of sample concentrations from several field sites. The laboratory alternates between analyzing a triplicate set consecutively and separating the triplicate set over a day or multiple day's analytical runs.

U.S. Geological Survey's Standard Reference Sample Project

The USGS Standard Reference Sample (SRS) Project conducts a national interlaboratory analytical evaluation program semiannually. The Troy Laboratory participates in the low-ionic-strength, nutrient, and trace components of this program. Typically, the reference samples consist of snow, rain, surface water, or deionized water that is collected, filtered, and possibly spiked with reagent-grade chemicals to meet the goals of the program. Reference samples for low-ionic-strength constituents are prefixed by a P and are analyzed for calcium, chloride, fluoride, magnesium, pH, potassium, sodium, specific conductance, and sulfate. Reference samples for nutrient constituents are prefixed by an N and are analyzed for ammonium. Reference samples for trace constituents are prefixed by a T and are analyzed for aluminum, calcium, magnesium, potassium, silicon, and sodium. Laboratory personnel are aware of the presence of the SRS sample at the time of analysis but do not know the constituent concentrations until a published report is received from the USGS after the conclusion of each study. The most probable value (MPV) for each constituent is equal to the median value calculated from the results submitted by participating laboratories. Laboratory performance is rated numerically by comparing analysis results to the MPVs for each constituent; the highest score is 4.0, and the lowest is 0.0.

4 Quality-Assurance Data for Routine Water Analyses by the USGS Laboratory in Troy, New York, July 1999 through June 2001

Table 1. Number of environmental and quality-control (QC) samples analyzed by the Troy Laboratory, and summary of quality-control data for each constituent, July 1999 through June 2001.

[QC-high, high concentration quality-control sample; QC-low, low concentration quality-control sample]

| Constituent | Number | lumber of samples analyzed | | Number of QC samples exceeding control limits where environmental | | Number of QC samples exceeding control limits by more than 5 percent where | |
|---|--------------------------|----------------------------|-------------------|---|--------|--|--------|
| | Environmental samples | QC-high samples | QC-low samples | sample data are not rejected | | environmental sample data are not rejected | |
| | pies | p | p | QC-high | QC-low | QC-high | QC-low |
| Acid-neutralizing capacity | 5,067 | 161 | 424 | 0 | 21 | 0 | 0 |
| Aluminum, total monomeric | 4,739 | 623 | 623 | 1 | 1 | 0 | 0 |
| Aluminum, organic mono- meric ¹ | 4,746 | 0 | 0 | 0 | 0 | 0 | 0 |
| Aluminum, total | 5,471 | 718 | 717 | 0 | 0 | 0 | 0 |
| Ammonium | 4,521 | 840 | 837 | 0 | 2 | 0 | 0 |
| Calcium | 5,227 | 655 | 655 | 0 | 0 | 0 | 0 |
| Carbon, dissolved organic | 5,068 | 804 | 805 | 6 | 7 | 6 | 6 |
| Chloride | 5,303 | 861 | 866 | 0 | 0 | 0 | 0 |
| Fluoride | 1,384 | 0 | 174 ² | 0 | 0 | 0 | 0 |
| Magnesium | 5,226 | 656 | 655 | 0 | 0 | 0 | 0 |
| Nitrate (ion chromatography) | 5,212 | 878 | 882 | 0 | 1 | 0 | 0 |
| Nitrate (colorimetric method) | 620 | 285 | 285 | 2 | 0 | 0 | 0 |
| pH | 5,108 | 233 | 521 | 3 | 16 | 0 | 0 |
| Potassium | 5,223 | 741 | 741 | 2 | 6 | 0 | 1 |
| Silicon | 5,228 | 654 | 655 | 0 | 1 | 0 | 0 |
| Sodium | 5,224 | 658 | 658 | 6 | 5 | 4 | 3 |
| Specific conductance | 4,054 | 0 | 479 | 0 | 6 | 0 | 0 |
| Sulfate | 5,304 | 1006 | 1011 | 0 | 0 | 0 | 0 |

¹Column efficiency is used to determine the acceptability of the data.

²Mid-level QC samples are used for fluoride.

NWRI Ecosystem Interlaboratory QA Program

The Troy Laboratory participates in Environment Canada's National Water Research Institute (NWRI) Ecosystem Interlaboratory QA program, in which a set of 10 samples is analyzed twice yearly. The samples are obtained from predominantly low-ionic-strength waters from several sources such as precipitation, snow, lakes, and streams throughout North America. The concentrations of the constituents in the NWRI samples are similar to those of the environmental samples analyzed at the Troy Laboratory. Laboratory results are compared with a median concentration value (MCV) calculated from results from all participants in the NWRI program. Laboratory personnel are aware of the presence of NWRI samples at the time of analysis but do not know the MCV of the constituents until Environment Canada publishes a report at the conclusion of each study.

Blind Reference Samples

The Troy Laboratory disguises USGS SRS samples from previous studies as routine environmental samples. These blind reference samples are processed and analyzed as environmental samples, and therefore appear to the analyst to be project samples. The blind reference samples have most probable values that were reported by the USGS SRS project. The SRS samples are rotated as supplies are exhausted, and periodically the identity of the blind reference sample is changed. One blind reference sample is included in each set of 50 environmental samples. The Troy Laboratory used SRS P-samples as the blind reference samples during the time period represented in this report.

(1)

Control-Chart Evaluation

Control charts (figs. 1–5, p. 14–27) are plots of QC data through time. This report uses control charts to (1) indicate whether the laboratory DQOs are met for individual QC samples; (2) reveal long-term biases within and outside the control limits; and (3) provide comparisons with results from other laboratories.

Each analyte has prescribed control limits that have been established to meet project DQOs (table 2). A constituent analysis is considered biased if 70 percent or more of the points on a chart are above or below the target value.

Quality-Control Samples

QC sample-analysis data are plotted on control charts (fig. 1) in which the central line is equal to the target value of the control sample. The control limits for the samples are represented by the upper and lower control-limit lines on each chart. QC-high and QC-low samples are plotted on separate graphs by constituent and date of analysis, and the control charts are evaluated for trends and (or) bias and precision. All data are reported in micromoles per liter (μ mol/L) except for pH (pH units), ANC (microequivalents per liter, μ eq/L), and specific conductance (microsiemens per centimeter, μ S/cm).

Filter Blanks and Analytical Blanks

Results from the blank analyses are plotted on control charts by constituent in figure 2. The control limits are represented by horizontal lines on the control charts. Data are plotted as concentration in relation to date of collection. Negative blank concentrations are encountered frequently. During analysis, the instrument calibration curve is extrapolated beyond the lowest standard in order to evaluate blank samples, and negative concentrations reflect the practical limitations of the extrapolation. An outlier on the control chart indicates possible contamination.

Triplicate Environmental Samples

The coefficient of variation (CV) for each triplicate sample concentration is plotted by constituent and date of collection in figure 3. Data with mean concentrations less than the defined reporting limit (table 2) are excluded. The DQO for all constituents is a CV of less than 10 percent, with the exception of ANC, total monomeric aluminum, organic monomeric aluminum, total aluminum, and ammonium, for which it is 15 percent. Each circle within the control charts represents the CV of a triplicate environmental sample. where

S = standard deviation,

and

 \overline{X}

= arithmetic mean of triplicate samples.

The ANC data are plotted on two graphs. The first (fig. 3A1) shows the *CV* for triplicate sample means *outside* the range of \pm 20-µeq/L; the absolute value of the mean is used to calculate the *CV*. The second (fig. 3A2) shows values *within* \pm 20-µeq/L; each symbol on the second graph represents the difference between the triplicate sample mean and the individual values of that triplicate sample.

 $CV = \frac{S}{\overline{V}}(100)$,

NWRI Ecosystem Interlaboratory QA Program

Interlaboratory-comparison graphs (fig. 4) are based on results from NWRI samples and represent NWRI studies from September 1999 through April 2001. Sample data with MCVs less than the Troy Laboratory reporting limits were excluded. The MCV and the control limits are represented by lines on the graphs; the percent difference (D) is calculated as:

$$D = \left[\left(AV - MCV \right) / MCV \right] \times 100 , \qquad (2)$$

where

and

AV

ICV mean and

MCV = mean concentration value.

= analyzed value,

A separate graph is shown for ANC values within the ± 20 -µeq/L range (fig. 4A2); these results are plotted as the difference between the laboratory value and the MCV. The pH results consist of two sets of data—values less than 6.00, and values equal to or greater than 6.00. The two sets of data have different DQOs, which are represented by a short dashed line and a long dashed line on the pH graph (fig. 4I).

Blind Reference Samples

Results from blind reference sample analyses are plotted in figure 5 by constituent and date of analysis. Sample data with MPVs less than the reporting limits were excluded. The MPV and the control limits of ± 10 percent are represented by lines on the graphs; the percent difference (*D*) is calculated as:

$$D = \left[\left(AV - MPV \right) / MPV \right] \times 100 \quad , \tag{3}$$

where

and

AV = analyzed value,

MPV = most probable value.

6 Quality-Assurance Data for Routine Water Analyses by the USGS Laboratory in Troy, New York, July 1999 through June 2001

Table 2. Reporting limits and data-quality objectives for accuracy, precision, and blanks for solution analyses

 performed by the U.S. Geological Survey Laboratory in Troy, N.Y., July 1999 through June 2001.

[DQO, data-quality objective; µmol/L, micromoles per liter; CV, coefficient of variation; ANC, acid-neutralizing capacity]

| | | | Accu | racy | | Precision | |
|--|-----------|---|---------------------------|---|---------------------------|-----------------------------------|--------------------------|
| Constituent or property | Reporting | Low-concentration quality-control sample | | High-concentration quality-control sample | | Environmental | Filter and analytical |
| | (µmol/L) | DQO (percent error) | Concentration (µmol/L) | DQO (percent error) | Concentration (µmol/L) | triplicate samples DQO (CV) | blanks DQO (µmol/L) |
| Acid-neutralizing capacity ¹ | none | 10 | (-39.9) | 10 | (125) | 15 | none |
| Aluminum, total monomeric | 1.5 | 15 | 7.41 | 10 | 18.5 | 15 | 1.0 |
| Aluminum, organic monomeric ² | 1.5 | none | none | none | none | 15 | 1.0 |
| Aluminum, total | 1.0 | 20 | 1.49 | 10 | 11.2 | 15 | 1.0 |
| Ammonium | 2.0 | 15 | 7.14 | 10 | 17.9 | 15 | 1.5 |
| Calcium | 2.0 | 10 | 25.0 | 10 | 99.8 | 10 | 1.0 |
| Carbon, dissolved organic ³ | 41.0 | 15 | 83.3 | 10 | 416 | 10 | 18 |
| Chloride | 3.0 | 10 | 8.47 | 10 | 84.7 | 10 | 2.0 |
| Fluoride | 0.5 | 15 | 1.58 | none | none | 10 | 0.5 |
| Magnesium | 1.0 | 10 | 10.3 | 10 | 41.1 | 10 | 0.5 |
| Nitrate (ion chromatography) | 2.0 | 10 | 4.84 | 10 | 48.4 | 10 | 0.3 |
| Nitrate (colorimetric method) | 5.0 | 15 | 42.9 | 10 | 100 | none | none |
| pH^4 | none | 10 | (4.44) | 20 | (6.88) | 10 | none |
| Potassium | 1.0 | 10 | 6.40 | 10 | 25.6 | 10 | 0.5 |
| Silicon | 6.0 | 10 | 35.6 | 10 | 107 | 10 | 3.0 |
| Sodium | 1.0 | 10 | 10.9 | 10 | 43.5 | 10 | 1.0 |
| Specific conductance ⁵ | none | 10 | (17.0) | 10 | (39.0) | 10 | 1.5 |
| Sulfate | 2.0 | 10 | 8.33 | 10 | 83.3 | 10 | 0.3 |

¹ANC: values in parentheses are in microequivalents per liter. For values within ± 20 microequivalents per liter, an absolute data-quality objective of ± 6 microequivalents per liter is used for precision.

²Quality-control samples for organic monomeric aluminum are unavailable.

³Concentrations are expressed as micromoles carbon per liter.

⁴pH: percent error and coefficient of variation are calculated from [H⁺]. Values in parentheses are in pH units.

⁵Specific conductance: values in parentheses are in microsiemens per centimeter.

Summary of Results

The following sections summarize the results for (A) quality-control samples (fig. 1, p. 14–18), (B) filter blanks and analytical blanks (fig. 2, p. 19–20), (C) triplicate environmental samples (fig. 3, p. 21–23), (D) SRS samples (table 3), (E) NWRI samples (fig. 4, p. 24–25), and (F) blind samples (fig. 5, p. 26–27).

A. Quality-Control Samples

- Acid-Neutralizing Capacity (fig. 1A)—DQOs were met by 96 percent of the samples. The QC-high sample had a negative bias through July 2000. No apparent trends or biases were evident for the QC-low sample.
- **Aluminum, Total Monomeric** (fig. 1B)—DQOs were met by 99 percent of the samples. The QC-low sample had a slight positive bias through 2000.

Aluminum, Organic Monomeric—A QC sample has not been developed for this analysis. Separation-column efficiency is used to determine acceptability of the data.

Aluminum, Total (fig. 1C)—DQOs were met by 100 percent of the samples. The QC-high sample had a positive bias during this period; the QC-low sample had a positive bias through May 2000.

Ammonium (fig. 1D)—DQOs were met by 99 percent of the samples. No apparent trends or biases were evident during this period.

Calcium (fig. 1E)—DQOs were met by 100 percent of the samples. The QC-high sample had a slight positive bias in 2001; the QC-low sample had a negative bias during this period.

Carbon, Dissolved Organic (fig. 1F)—DQOs were met by 99 percent of the samples. The QC-high sample had a negative bias during this period. No apparent trends or biases were evident for the QC-low sample.

Chloride (fig. 1G)—DQOs were met by 100 percent of the samples. The QC-high sample had a negative bias from November 1999 through November 2000; the remaining time it indicated a positive bias. No apparent trends or biases were evident for the QC-low sample.

Fluoride (fig. 1H)—DQOs were met by 100 percent of the samples. No apparent trends or biases were evident during this period.

Magnesium (fig. 1I)—DQOs were met by 100 percent of the samples. The QC-high sample had a positive bias and the QC-low sample had a negative bias during this period.

Nitrate (ion chromatography) (fig. 1J)—DQOs were met by 99 percent of the samples. The QC-high sample had a negative bias from November 1999 through November 2000; the remaining time it indicated a positive bias. No apparent trends or biases were evident for the QC-low sample.

Nitrate (colorimetric method) (fig. 1K)—DQOs were met by 99 percent of the samples. The QC-high and QC-low samples had a negative bias in 2000.

pH (fig. 1L)—DQOs were met by 97 percent of the samples. No apparent trends or biases were evident during this period.

Potassium (fig. 1M)—DQOs were met by 99 percent of the samples. No apparent trends or biases were evident during this period.

Silicon (fig. 1N)—DQOs were met by 99 percent of the samples. No apparent trends or biases were evident during this period.

Sodium (fig. 10)—DQOs were met by 99 percent of the samples. No apparent trends or biases were evident during this period.

Specific conductance (fig. 1P)—DQOs were met by 99 percent of the samples. The QC-high concentration sample was not analyzed during period. The QC-low sample had a negative bias from May 2000 through April 2001.

Sulfate (fig. 1Q)—DQOs were met by 100 percent of the samples. The QC-high sample had a negative bias from November 1999 through November 2000; the remainder of the period it indicated a positive bias. No apparent trends or biases were evident for the QC-low sample.

B. Filter Blanks and Analytical Blanks

- Acid-Neutralizing Capacity—Blanks were not analyzed for this constituent during this period.
- **Aluminum, Total Monomeric** (fig. 2A)—The DQO was met by 99 percent of the samples. No systematic trends were evident for this analysis.
- **Aluminum, Organic Monomeric** (fig. 2B)—The DQO was met by 100 percent of the samples. No systematic trends were evident for this analysis.
- **Aluminum, Total** (fig. 2C)—The DQO was met for 92 percent of the samples. No systematic trends were evident for this analysis.

Ammonium (fig. 2D)—The DQO was met by 91 percent of the samples. No systematic trends were evident for this analysis.

Calcium (fig. 2E)—The DQO was met by 98 percent of the samples. No systematic trends were evident for this analysis.

Carbon, Dissolved Organic (fig. 2F)—The DQO was not met for DOC. Blank data results are significantly higher in DOC concentrations since a new instrument was purchased in 1998. The current DQO is being evaluated.

Chloride (fig. 2G)—The DQO was met by 82 percent of the samples. The chloride contamination problem has continued to improve.

Fluoride (fig. 2H)—The DQO was met by 100 percent of the samples. No systematic trends were evident for this analysis.

Magnesium (fig. 2I)—The DQO was met by 100 percent of the samples. No systematic trends were evident for this analysis.

8 Quality-Assurance Data for Routine Water Analyses by the USGS Laboratory in Troy, New York, July 1999 through June 2001

Nitrate (ion chromatography) (fig. 2J)—The DQO was met by 92 percent of the samples. No systematic trends were evident for this analysis.

Nitrate (colorimetric method)—Blanks were not available for this constituent during this period.

pH—Blanks were not analyzed for this constituent during this period.

Potassium (fig. 2K)—The DQO was met by 92 percent of the samples. No systematic trends were evident for this analysis.

Silicon (fig. 2L)—The DQO was met by 100 percent of the samples. No systematic trends were evident for this analysis.

Sodium (fig. 2M)—The DQO was met by 94 percent of the samples. No systematic trends were evident for this analysis.

Specific conductance (fig. 2N)—The DQO was met by 80 percent of the samples. No systematic trends were evident for this analysis.

Sulfate (fig. 2O)—The DQO was met by 98 percent of the samples. No systematic trends were evident for this analysis.

C. Triplicate Environmental Samples

Acid-Neutralizing Capacity (figs. 3A1 and 3A2)—The DQO was met by 96 percent of the triplicate samples.

Aluminum, Total Monomeric (fig. 3B)—The DQO was met by 96 percent of the triplicate samples.

Aluminum, Organic Monomeric (fig. 3C)—The DQO was met by 100 percent of the triplicate samples.

Aluminum, Total (fig. 3D)—The DQO was met by 90 percent of the triplicate samples.

Ammonium (fig. 3E)—The DQO was met by 81 percent of the triplicate samples.

Calcium (fig. 3F)—The DQO was met by 100 percent of the triplicate samples.

Carbon, Dissolved Organic (fig. 3G)—The DQO was met by 92 percent of the triplicate samples.

Chloride (fig. 3H)—The DQO was met by 75 percent of the triplicate samples.

Fluoride (fig. 3I)—The DQO was met by 91 percent of the triplicate samples.

Magnesium (fig. 3J)—The DQO was met by 100 percent of the triplicate samples.

Nitrate (ion chromatography) (fig. 3K)—The DQO was met by 95 percent of the triplicate samples.

Nitrate (colorimetric method)—Triplicate samples were not available for this constituent during this period.

pH (fig. 3L)—The DQO was met by 100 percent of the triplicate samples.

Potassium (fig. 3M)—The DQO was met by 95 percent of the triplicate samples.

Silicon (fig. 3N)—The DQO was met by 100 percent of the triplicate samples.

Sodium (fig. 30)—The DQO was met by 86 percent of the triplicate samples.

Specific conductance (fig. 3P)—The DQO was met by 91 percent of the triplicate samples.

Sulfate (fig. 3Q)—The DQO was met by 100 percent of the triplicate samples.

D. U.S. Geological Survey's Standard Reference Sample (SRS) Project

The U.S. Geological Survey's SRS Project rates laboratory performance for each analyte on a scale of 4 to 0:

| Rating | Performance |
|----------|--------------------|
| 4.0 | Excellent |
| 3.0-3.99 | Good |
| 2.0-2.99 | Satisfactory |
| 1.0-1.99 | Marginal |
| 0.0-0.99 | Unsatisfactory |

Overall laboratory mean ratings for each SRS sample were:

| P-34 3.6 | T-161 3.0 | N-63 3.0 |
|----------|-----------|----------|
| P-35 3.9 | T-163 3.2 | N-65 3.0 |
| | | N-67 4.0 |

Missing SRS results for the Troy Laboratory were due to instrument failure during the SRS study period. The laboratory did not submit results for the SRS samples distributed in April 2001.

All analyses received a satisfactory or better rating for each constituent with one exception:

Sodium—The cause of a zero rating for SRS T-161 is erroneous data entry.

Table 3. Results obtained by the Troy Laboratory for the U.S. Geological Survey Standard Reference Sample (SRS) Project, October 1999 through October 2000.

[MPV, most probable value; TV, Troy Laboratory value. All values are in milligrams per liter except aluminum (µg/L), pH (pH units) and specific conductance (microsiemens per centimeter); --, dashes indicate no results reported]

| | MPV, | | SRS sample number and date of sample distribution | | | | | |
|-----------------------|-------------------------|--------------------|---|--------|--------|--------------------|--------------------|---------------------------|
| Analyte | rte TV, N-63 T-161 | N-65 P-34 | | T-163 | N-67 | P-35 | | |
| | and rating ^a | 10-99 ^b | 03-00° | 03-00° | 03-00° | 10-00 ^d | 10-00 ^d | 10-00 ^d |
| Aluminum | MPV | | 38.4 | | | 16.8 | | |
| | TV | | 38.3 | | | 14.54 | | |
| | Rating | | 3 | | | 2 | | |
| Ammonium ^e | MPV | 0.150 | | 0.124 | | | 0.433 | |
| | TV | 0.165 | | 0.142 | | | 0.4466 | |
| | Rating | 3 | | 3 | | | 4 | |
| Calcium | MPV | | 7.17 | | 1.63 | 6.30 | | 0.541 |
| | TV | | 7.10 | | 1.58 | 6.45 | | 0.522 |
| | Rating | | 4 | | 3 | 4 | | 4 |
| Chloride | MPV | | | | 4.18 | | | 5.31 |
| | TV | | | | 4.22 | | | 5.032 |
| | Rating | | | | 4 | | | 3 |
| Magnesium | MPV | | 1.51 | | 0.592 | 1.23 | | 0.090 |
| | TV | | 1.51 | | 0.577 | 1.299 | | 0.089 |
| | Rating | | 4 | | 4 | 3 | | 4 |
| эΗ | MPV | | | | 4.32 | | | 4.89 |
| | TV | | | | 4.32 | | | 4.96 |
| | Rating | | | | 4 | | | 4 |
| Potassium | MPV | | 1.26 | | 0.238 | 1.02 | | 0.184 |
| oussium | TV | | 1.36 | | 0.230 | 1.08 | | 0.1786 |
| | Rating | | 3 | | 4 | 4 | | 4 |
| Silicon ^f | MPV | | 14.8 | | | 4.56 | | |
| Jincon | TV | | 14.8 | | | 4.759 | | |
| | Rating | | 4 | | | 3 | | |
| | MPV | | 43.0 | | 0.439 | | | 3.00 |
| Sodium | TV | | 3.8 | | 0.450 | | | 2.995 |
| Jourum | Rating | | 0 | | 4 | | | 4 |
| Specific conduc- | MPV | | | | 41.8 | | | 27.0 |
| tance | TV | | | | 39.4 | | | 26.05 |
| tunce | Rating | | | | 2 | | | 4 |
| | MPV | | | | 0.437 | | | 0.673 |
| Sulfate | TV | | | | 0.437 | | | 0.675 |
| Junate | Rating | | | | 4 | | | 4 |

^aLaboratory rating system: 4 is highest score; 0 is lowest.

^bSample described in Farrar (2000).

^cSample described in Farrar and Copen (2000).

^dSample described in Connor, Currier, and Woodworth (2001).

"The SRS Project reports data as "Ammonia as Nitrogen."

^fThe SRS Project reports data as "Silica."

E. NWRI Ecosystem Interlaboratory QA Program

Environment Canada's NWRI program does not audit the analysis of total monomeric aluminum, organic monomeric aluminum, fluoride, and nitrate (colorimetric method).

Acid-Neutralizing Capacity (figs. 4A1–4A2)—The DQO was met by 90 percent of the NWRI samples. No trend or bias was evident. Data were not submitted for study 77 due to instrument failure.

Aluminum, Total (fig. 4B)—The DQO was met by 50 percent of the NWRI samples. The cause of the erratically high outliers is unknown.

Ammonium (fig. 4C)—The DQO was not met for the NWRI samples. The cause of the positive bias is currently being investigated. The reporting limit for ammonium is being reevaluated.

Calcium (fig. 4D)—The DQO was met by 98 percent of the NWRI samples. No trend or bias was evident.

Carbon, Dissolved Organic (fig. 4E)—The DQO was met by 62 percent of the NWRI samples. The data exhibited a positive bias for studies 75 and 78. The cause is unknown.

Chloride (fig. 4F)—The DQO was met by 90 percent of the NWRI samples. The data exhibited a negative bias during studies 76 and 78.

Magnesium (fig. 4G)—The DQO was met by 100 percent of the NWRI samples. The data exhibited a slight positive bias during studies 75 and 78 and a slight negative bias during studies 76 and 77.

Nitrate (ion chromatography) (fig. 4H)—The DQO was met by 89 percent of the NWRI samples. No trend or bias was evident.

pH (fig. 4I)—The DQO was met by 100 percent of the NWRI samples. No trend or bias was evident. Data were not submitted for study 77 due to instrument failure.

Potassium (fig. 4J)—The DQO was met by 98 percent of the NWRI samples. The data exhibited a positive bias during studies 75, 76, and 77.

Silicon (fig. 4K)—The DQO was met by 100 percent of the NWRI samples. No trend or bias is evident.

Sodium (fig. 4L)—The DQO was met by 73 percent of the NWRI samples. The cause of the erratically high outliers is unknown.

Specific Conductance (fig. 4M)—The DQO was met by 97 percent of the NWRI samples. The data exhibited a negative bias during study 76. Data were not submitted for study 77 due to instrument failure.

Sulfate (fig. 4N)—The DQO was met by 98 percent of the NWRI samples. The data exhibited a slight negative bias for studies 76 and 77.

F. Blind Reference Samples

Blind reference samples (SRS low-ionic-strength constituent P-samples) are analyzed for the Troy Laboratory procedures for which the SRS project reports an analyte MPV. The blind reference samples are not analyzed for acidneutralizing capacity, total monomeric aluminum, organic monomeric aluminum, total aluminum, ammonium, dissolved organic carbon, nitrate and silicon.

- **Calcium** (fig. 5A)—The DQO for calcium was met by 95 percent of the blind reference samples. The data exhibited a negative bias for this period.
- **Chloride** (fig. 5B)—The DQO was met by 100 percent of the blind reference samples. A negative bias was evident through 1999.

Fluoride (fig. 5C)—The DQO was met by 100 percent of the blind reference samples. The laboratories began fluoride analysis on blind reference samples in 2001.

- **Magnesium** (fig. 5D)—The DQO was met by 94 percent of the blind reference samples. Most data indicated a negative bias.
- **pH** (fig. 5E)—The DQO was met by 91 percent of the blind reference samples. A slight positive bias was evident during 1999 and again in 2001.

Potassium (fig. 5F)—The DQO was met by 93 percent of the blind reference samples. No trend or bias was evident.

Sodium (fig. 5G).—The DQO was met by 75 percent of the blind reference samples. The cause of the negative bias is unknown.

Specific conductance (fig. 5H)—The DQO was met by 58 percent of the blind reference samples. A negative bias is evident.

Sulfate (fig. 5I)—The DQO was met by 100 percent of the samples. No trend or bias was evident.

Selected References

- Connor, B.F., Currier, J.P., and Woodworth, M.T., 2001, Results of the U.S. Geological Survey's analytical evaluation program for standard reference samples distributed in October 2000: U.S. Geological Survey Open-File Report 01–137, 116 p.
- Farrar, J.W., 2000, Results of the U.S. Geological Survey's analytical evaluation program for standard reference samples distributed in October 1999: U.S. Geological Survey Open-File Report 00–227, 107 p.
- Farrar, J.W. and Copen, A.M., 2000, Results of the U.S.
 Geological Survey's analytical evaluation program for standard reference samples distributed in March 2000: U.S.
 Geological Survey Open-File Report 00–398, 107 p.
- Lawrence, G.B., Lincoln, T.A., Horan-Ross, D.A., Olson,
 M.L., and Waldron, L.A., 1995, Analytical methods of the
 U.S. Geological Survey's New York District Water Analysis
 Laboratory: U.S. Geological Survey Open-File Report
 95–416, 78 p.
- Lee, M.P., 1996, U.S. Geological Survey water-resources programs in the New York District—fiscal years 1993–94: U.S. Geological Survey Open-File Report 96–113, 48 p.

- Lincoln, T.A., Horan-Ross, D.A., Olson, M.L., and Lawrence, G.B., 1996, Quality-assurance data for routine water analyses by the U.S. Geological Survey Laboratory in Troy, New York: May 1991 through June 1993: U.S. Geological Survey Open-File Report 96–167, 22 p.
- Lincoln, T.A., Horan-Ross, D.A., McHale, M.R., and Lawrence, G.B., 2001, Quality-assurance data for routine water analyses by the U.S. Geological Survey Laboratory in Troy, New York: July 1993 through June 1995: U.S. Geological Survey Open-File Report 01–171, 25 p.
- Lincoln, T.A., Horan-Ross, D.A., McHale, M.R., and Lawrence, G.B., 2004, Quality-assurance data for routine water analyses by the U.S. Geological Survey Laboratory in Troy, New York: July 1995 through June 1997: U.S. Geological Survey Open-File Report 2004–1327, 25 p.
- Lincoln, T.A., Horan-Ross, D.A., McHale, M.R., and Lawrence, G.B., 2006, Quality-assurance data for routine water analyses by the U.S. Geological Survey Laboratory in Troy, New York: July 1997 through June 1999: U.S. Geological Survey Open-File Report 2006–1245, 25 p.

12 Quality-Assurance Data for Routine Water Analyses by the USGS Laboratory in Troy, New York, July 1999 through June 2001

Figures 1–5




Figure 1. High- and low-concentration quality-control sample results: *A*. Acid-neutralizing capacity. *B*. Aluminum, total monomeric. *C*. Aluminum, total. *D*. Ammonium.




Figure 1. High- and low-concentration quality-control sample results: *E*. Calcium. *F*. Carbon, dissolved organic. *G*. Chloride. *H*. Fluoride.—Continued




Figure 1. High- and low-concentration quality-control sample results: *I*. Magnesium. *J*. Nitrate (ion chromatography). *K*. Nitrate (colorimetric method). *L*. pH.—Continued





Figure 1. High- and low-concentration quality-control sample results: *M*. Potassium. *N*. Silicon. *O*. Sodium. *P*. Specific conductance.—Continued



O CONTROL SAMPLE

- TARGET VALUE ------

----- UPPER CONTROL LIMIT

— — — LOWER CONTROL LIMIT




Figure 2. Filter-blank and analytical-blank sample results: *A*. Aluminum, total monomeric. *B*. Aluminum, organic monomeric. *C*. Aluminum, total. *D*. Ammonium. *E*. Calcium. *F*. Carbon, dissolved organic. *G*. Chloride. *H*. Fluoride.




Figure 2. Filter-blank and analytical-blank sample results: *I.* Magnesium. *J.* Nitrate (ion chromatography). *K.* Potassium. *L.* Silicon. *M.* Sodium. *N.* Specific conductance *O.* Sulfate.—Continued




Figure 3. Triplicate environmental sample results: *A1.* Acid-neutralizing capacity (for triplicate means not in ±20 µeq/L range). *A2.* Acid-neutralizing capacity (for triplicate means in ±20 µeq/L range). *B.* Aluminum, total monomeric. *C.* Aluminum, organic monomeric. *D.* Aluminum, total. *E.* Ammonium. *F.* Calcium. *G.* Carbon, dissolved organic.





Figure 3. Triplicate environmental sample results: *H*. Chloride. *I*. Fluoride. *J*. Magnesium. *K*. Nitrate (ion chromatography) . *L*. pH. *M*. Potassium. *N*. Silicon. *O*. Sodium—Continued



• COEFFICIENT OF VARIATION ----- CONTROL LIMIT

Figure 3. Triplicate environmental sample results: P. Specific conductance. Q. Sulfate.—Continued




Figure 4. NWRI Ecosystem Interlaboratory QA Program results: *A1.* Acid-neutralizing capacity (for samples not in the range of ± 20 µeq/L). *A2.* Acid-neutralizing capacity (for samples in the range of ± 20 µeq/L). *B.* Aaluminum, total. *C.* Ammonium. *D.* Calcium. *E.* Carbon, dissolved organic. *F.* Chloride. *G.* Magnesium.




Figure 4. NWRI Ecosystem Interlaboratory QA Program results: *H*. Nitrate (ion chromatography). *I*. pH. *J*. Potassium. *K*. Silicon. *L*. Sodium. *M*. Specific conductance. *N*. Sulfate.—Continued.





Figure 5. Blind reference sample results: *A.* Calcium. *B.* Chloride. *C.* Fluoride. *D.* Magnesium. *E.* pH. *F.* Potassium. *G.* Sodium. *H.* Specific conductance.





O PERCENT DIFFERENCE ______ TARGET VALUE ____ UPPER CONTROL LIMIT _____ LOWER CONTROL LIMIT

This page has been left blank intentionally.

For additional information write to: New York Water Science Center U.S. Geological Survey 2045 Route 112, Bldg. 4 Coram, NY 11727

Information requests: (518) 285-5602 or visit our Web site at: http://ny.water.usgs.gov

≥USGS Lincoln, Horan-Ross, McHale, and Lawrence—Quality-Assurance Data for Routine Water Analyses by the—Open-File Report 2006–1246 U.S. Geological Survey Laboratory in Troy, New York— July 1999 through June 2001