
U.S. DEPARTMENT OF THE INTERIOR
U.S. GEOLOGICAL SURVEY

OPEN-FILE REPORT 2007–1411
Version 1.0





EXPLANATION

- Intermittent streams
- Perennial streams
- Minimum length of main channel that can be impacted by debris flows generated from delineated basins
- Major Roads
- Streets
- Towns

Volume of debris flow (m^3)

(in response to 2.25 inches (57.15 mm) of rainfall in 3 hours)

- 1–1,000
- 1,001–10,000
- 10,001–100,000
- >100,000
- Fire perimeter

These maps are not to be used for flood insurance rating purposes under the National Flood Insurance Program. For insurance rating purposes, please refer to the currently effective Flood Insurance Rate Maps (FIRM) published by the Federal Emergency Management Agency (FEMA). To obtain a copy of the FIRM, contact the FEMA Map Service Center at (800) 358-9616, or at http://msc.fema.gov

This report is preliminary and has not been reviewed for conformity with U.S. Geological Survey editorial standards or with the North American Stratigraphic code.

Any use of trade, firm, or product names is for descriptive purposes only, and does not imply endorsement by the U.S. Government.

Permission must be secured from the individual copyright owners to reproduce any copyrighted material contained within this report.

For sale by U.S. Geological Survey Information Services
Box 25286, Federal Center, Denver, CO 80225
1-888-ASK-USGS

A PDF of this report is available at: http://pubs.usgs.gov/of/2007/1411

EMERGENCY ASSESSMENT OF DEBRIS-FLOW HAZARDS FROM BASINS BURNED BY THE 2007 POOMACHA FIRE, SAN DIEGO COUNTY, SOUTHERN CALIFORNIA

By

Susan H. Cannon,[1] Joseph E. Gartner, John A. Michael, Mark A. Bauer, Susan C. Stitt, Donna L. Knifong, Bernard J. McNamara, and Yvonne M. Roque

[1]U.S. Geological Survey, Box 25046, DFC, MS 966, Denver CO 80225, (303) 273-8604, cannon@usgs.gov

2007

Introduction

The objective of this report is to present a preliminary emergency assessment of the potential for debris-flow generation from basins burned by the Poomacha Fire in San Diego County, southern California in 2007. Debris flows are among the most hazardous geologic phenomena (Turner and Schuster, 1996); debris flows that followed wildfires in southern California in 2003 killed 16 people and caused tens of millions of dollars of property damage (NOAA-USGS Debris Flow Task Force, 2005). A short period of even moderate rainfall on a burned watershed can lead to debris flows (Cannon and others, 2008). Rainfall that is normally absorbed into hillslope soils can run off almost instantly after vegetation has been removed by wildfire. This causes much greater and more rapid runoff than is normal from creeks and drainage areas. Highly erodible soils in a burn scar allow flood waters to entrain large amounts of ash, mud, boulders, and unburned vegetation. Within the burned area and downstream, the force of rushing water, soil, and rock can destroy culverts, bridges, roadways, and buildings, potentially causing injury or death.

This emergency debris-flow hazard assessment is presented as a relative ranking of predicted median volumes of debris flows that can issue from basin outlets in response to 2.25 inches (57.15 mm) of rainfall over a 3-hour period. Such a storm has a 10-year return period (Hershfield, 1961). The calculation of debris-flow volume is based on a multiple-regression statistical model that describes the median volume of material that can be expected from a recently burned basin as a function of the area burned at high and moderate severity, the basin area with slopes greater than or equal to 30 percent, and triggering storm rainfall (Gartner and others, 2008). Cannon and others (2007) describe the methods used to generate the hazard maps. Identification of potential debris-flow hazards from burned drainage basins is necessary to issue warnings for specific basins, to make effective mitigation decisions, and to help plan evacuation timing and routes.

Results

In response to the 10-year recurrence, 3-hour rainstorm, five of the 107 basins evaluated in this assessment were identified as having the potential to produce debris flows with volumes less than 1,000 m^3 and 84 of the basins evaluated showed the potential to produce debris flows with volumes between 1,001 and 10,000 m^3. These are small (0.02 to 5.4 km^2) basins that drain into the San Luis Rey River, Hell Creek, and Guejito Creek. Seventeen basins evaluated showed volume estimates between 10,000 and 100,000 m^3. From north to south, these include Seco Creek; Agua Tibia Creek; Frey Creek; two unnamed basins that drain into Long Canyon; Harrison Canyon; Yuima Creek; Plaisted Creek and an unnamed basin adjacent to Plaisted Creek; two unnamed basins through which South Grade Road travels; an unnamed basin adjacent to South Grade Road; Cedar Creek and the unnamed basin adjacent to Cedar Creek; two unnamed basins that drain into the San Luis Rey River; and the headwaters of Hell Creek. The basin that includes Lion Creek, French Creek, Doane Creek and Pauma Creek was identified as having the potential to produce debris flows with volumes greater than 100,000 m^3.

Debris flows issuing from these basins can impact the South Grade Road, Pala Road (State Highway 76), and Paradise Creek Road (S6). The towns of Pauma Valley, Rincon, and La Jolla Amago, in addition to other neighborhoods, buildings, and roads within any of the burned basins can be impacted by debris flows.

Use and Limitations of the Map

This map shows potential hazards posed by debris flows as estimates of median volumes of material that may issue from the outlets of basins burned by the Poomacha Fire of 2007 in southern California in response to a 10-year-recurrence, 3-hour-duration rainstorm. The map identifies the range of potential debris-flow volumes that can issue from individual basin outlets. This information can be used to issue warning for specific locations, to prioritize mitigation efforts, to aid in the design of mitigation structures, and to guide decisions for evacuation, shelter, and escape routes in the event that storms of similar magnitude to that evaluated here are forecast for the area.

In addition to the potential dangers within the basins, areas downstream from the basin outlets are also at risk. In some of these areas homes were destroyed by the fire, and workers and residents may be busy cleaning and rebuilding sites. The potential for debris flows during rainfall events places these people at high risk. In addition, if culverts are plugged or overwhelmed by flows, or if roads wash out, motorists may be stranded for long periods of time. In some cases, channels cross roads on blind curves where motorists could abruptly encounter debris-flow deposits on the road.

In addition to the colored drainage basins, small debris flows can be generated from non-colored areas within the burn perimeter. These areas were not included in the analysis because they are occupied by either planar hillslopes or basins that are smaller than those used in the model development (Cannon and others, 2007).

We expect that the map presented here may be applicable for approximately three years after the fires for the storm conditions considered. The potential for debris-flow activity decreases with time following fire and the concurrent revegetation and stabilization of hillslopes. A compilation of information on post-fire runoff events from throughout the western U.S. indicates that under normal rainfall conditions most debris-flow activity occurs within about two years following a fire. If dry conditions slow re-growth of vegetation, this recovery period will be longer. Our assessment is specific to post-fire debris flows; significant hazards from flash flooding can remain for many years after a fire.

This assessment is based on the assumption that all basins are equally prone to debris flows. Recent work has indicated that, in addition to the volume, the probability of debris flow will vary with burn severity, basin gradient, material properties and storm rainfall. Unfortunately, a determination of debris-flow probability cannot yet be incorporated into this hazard assessment.

Suggested Actions

People occupying businesses, homes, and recreational facilities downstream of the basins identified as the most hazardous must be informed of the potential dangers from debris flows and flooding. Warning must be given even for those basins with engineered mitigation structures at their mouths in the event that the structures are not adequate to contain potential debris flows. Site-specific debris-flow hazard assessments ought to be performed upslope from structures and facilities in areas identified as being at risk.

Because this assessment is specific to post-fire debris flows, further assessment of potential hazards posed by flash floods is needed. Continued operation of the early-warning system for both flash floods and debris flows established by NOAA's National Weather Service and the U.S. Geological Survey (http://www.wrh.noaa.gov/sgx/hydro/debris_flow.php; NOAA-USGS Debris Flow Task Force, 2005) would help local officials make decisions about evacuations and inform the public about potential dangers of debris flows in advance of rainfall events. The system consists of an extensive reporting rain-gage and stream-gage network coupled with National Weather Service weather forecasts and radar rainfall measurements. Any early-warning system should be coordinated with existing county and flood district facilities.

An evaluation of the effectiveness of hillslope and channel mitigation approaches focused on the ability of different treatment methods to decrease the potential volume of debris flows (deWolfe, 2006; deWolfe and others, 2008). This work found that extensive applications of treatments that promote rainfall infiltration into hillslopes combined with engineered works that control incision in low-gradient channel reaches can effectively mitigate debris-flow impacts in basins less than about two km^2 in area that are expected to produce debris-flow volumes of less than 10,000 m^3. Large engineered check dams or collection basins are necessary to effectively mitigate hazards posed by events from basins larger than about two km^2 that are expected to produce debris-flow volumes greater than about 10,000 m^3 (Hungr and others, 1987; Fiebiger, 1997; Okubo and others, 1997; Heumader, 2000; deWolfe, 2006).

References Cited

Cannon, S.H., Gartner, J.E., and Michael, J.A., 2007, Methods for the emergency assessment of debris-flow hazards from basins burned by the fires of 2007, southern California: U.S. Geological Survey Open-File Report 2007–1384, 10 p.

Cannon, S.H., Gartner, J.E., Wilson, R.C., and Laber, J.L., 2008, Storm rainfall conditions for floods and debris flows from recently burned areas in southwestern Colorado and southern California: Geomorphology, doi:10.1019/j.geomorph.2008.03.019.

deWolfe, V.G., 2006, An evaluation of erosion control methods after wildfire in debris-flow prone areas after wildfire: Golden, Colorado School of Mines, Department of Geology and Engineering Geology, M.S. thesis, 186 p.

deWolfe, V.G., Santi, P.M., Ey, John, and Gartner, J.E., 2008, Effective mitigation of debris flows at Lemon dam, La Plata County, Colorado: Geomorphology, doi:10.1016/j.geomorph.2008.04.008.

Fiebiger, G., 1997, Structures of debris-flow countermeasures, *in* Chen, C.I., ed., Debris Flow Hazards Mitigation—Mechanics, Prediction, and Assessment, Proceedings of First International Conference: New York, N.Y., American Society of Civil Engineers, p. 596–606.

Gartner, J.E., Cannon, S.H., Santi, P.M., and deWolf, V.G., 2008, Empirical models to predict debris flow volumes generated from recently burned basins in the western U.S.: Geomorphology, doi:10.1016/j.geomorph.2008.02.033.

Hershfield, D.M., 1961, Rainfall frequency atlas of the United States for durations from 30 minutes to 24 hours and return periods from 1 to 100 years: Technical Paper No. 40, U.S. Department of Commerce, Weather Bureau, 61 p.

Heumader, J., 2000, Technical debris flow countermeasures in Austria—A review, *in* Wieczorek, G.F., and Naeser, N.D., eds., Debris flow Hazards Mitigation—Mechanics, Prediction, and Assessment, Proceedings of Second International Conference on Debris Flow Hazards Mitigation: Taipei, Taiwan August 16–18, 2000, A.A. Balkema, Brookfield, Vt., p. 553–564.

Hungr, Oldrich, Morgan, G.C., VanDine, D.F., and Lister, D.R., 1987, Debris flow defenses in British Columbia, *in* Costa, J.E., and Wieczorek, G.F., eds., Debris Flows/Avalanches—Process, Recognition, and Mitigation: Reviews in Engineering Geology vol. VII, The Geological Society of America, Boulder, Colo., p. 201–222.

NOAA-USGS Debris Flow Task Force, 2005, NOAA-USGS debris-flow warning system–Final report: U.S. Geological Survey Circular 1283, 47 p.

Okubo, S., Ikeya, H., Ishikawa, Y., and Yamada, T., 1997, Development of new methods for countermeasures against debris flows, *in* Armani, A., and Michiue, M., eds., Recent Developments on Debris Flows, Lecture Notes in Earth Sciences, vol., 64, Springer-Verlag, New York, N.Y., p. 166–185.

Turner, A.K., and Schuster, R.L., eds, 1996, Landslides, investigation and mitigation, Transportation Research Board Special Report 247: Washington D.C., National Research Council, 673 p.